

IP-HIK02

2 Megapixel Wifi IP Camera 1/2.8"
Progressive Scan CMOS
Compression
H.265+/H.265/H.264+/H.264/MJPEG
2.8 mm Lens
IR LEDs Range 30 m
WEB, CMS Software, Smartphone
and NVR



Hikvision oem
IP camera
1/2.8" Progressive CMOS
2 Megapixel (1920x1080)
2.8 mm Wide Angle Lens
0 Lux - IR Range 30 m
Compression H.265+/H.265/H.264+/H.264/MJPEG
RJ-45 10/100 BaseT
Wifi IEEE 802.11b/g/n
PoE IEEE802.3af
IR Cut
WDR
SD card recording
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible

Specifications

| | |
|-----------------------------|---|
| Brand | Hikvision OEM |
| Image sensor | 1/2.8" Progressive CMOS |
| Maximum resolution | 2Mpx (1920x1080) |
| Main Stream rate | 1080p / 720p (1 ~ 25 FPS) |
| Extra Stream rate | D1 / VGA / CIF / QVGA (1 ~ 25 FPS) |
| Compression | H.265+/H.265/H.264+/H.264/MJPEG |
| Bitrate | 32 Kbps ~ 8 Mbps |
| Lens | 2.8 mm (136°) |
| Minimum illumination | 0.01 Lux @F1.2 (Colour) |
| Infrared lighting | 0.001 Lux / IR LED (30m) |
| Image improvements | WDR (120 dB), BLC, 3D-NR, MD, ROI, Line crossing and intrusion |
| Day / Night | Removable mechanical ICR filter |
| Network interface | Ethernet 10/100 BaseT, Wifi IEEE 802.11b/g/n |
| Internal memory | MicroSD Card, Max 128 GB (Not included) |
| Remote access | Web browser, Safire Control Center Smartphone App and PC Software |
| Interoperability | ONVIF, ISAPI |
| Power supply | DC 12 V / 400 mA, PoE IEEE802.3af |
| Degree of protection | Weatherproof IP67 |
| Temp. operation | -30° C ~ +60° C |
| Dimensions | 82 mm (H) x 111 (Ø) mm |
| Weight | 350 g |