



Key Features:

1. 2Megapixel. 1080P.
2. 2pcs IR leds, 2pcx white LED IR distance 20M. Lens 3.6mm
3. Wi-Fi/802.11/b/g/n ,Free PC CMS Software.
4. Motion detection, email alert, FTP upload
5. Support Video Mask and Special Area Dection
6. 12 languages, Firefox, Safari, Google,IE browser
7. Built-in IR Cut, No Color Cast.
8. P2P, PNP: Plug&play, Support QR code scanning to view on Iphone and android Mobiles
9. Support standard Onvif protocol, one key setting
10. Support Max 128G TF card

Ssystem	System Security	Supports there-level account, password, user authority management.
	OS	Embedded Linux OS
	Processor	Hi3518e, v200
	P2P (Free)	No need to preset camera, Offer free P2P, Plug&play, Support QR code scanning to view

	Onvif Protocol	Support ONVIF Protocol
	Multi-device function	Support 13 language remote surveillance, record, alarm, wifi setting etc.
	PC client	Support remote multi-devices monitor, record, alarm etc; Support Windows and Mac OS
	Cell Phone View	APP, Support iPhone,Android smart phone
	TF Card Record	Support max 128GB
Lens	Lens Type	3.6MM
	IR-CUT	Build-in IR CUT, no color cast,auto switch when IR on
Video	Image Compression	H.264/MJPEG
	Sensor	1/2.7" Progressive Scan 2MP CMOS
	Video Parameters	Brightness, Contrast,Saturation,Exposure,sharpness can be adjusted
	Image Frame Rate	50Hz:15fps/60HZ:15fps (1920x1080)
	First Stream	1080P(1920x1080), 960P(1280x960),720P(1280x720)
	Second Stream	-(640x352),(320x176)
	Third Stream	(320x176)
Night Vision	Night Visibility	. 2pcs IR leds, 2pcx white LED ,night vision up to 15~20 meters
	Lux	IR ON 0 LUX
Alarm	Motion Detect	Support 4 Independent detection areas(Sensitivity can be adjustd 1-100)
	Alarm Action	Support Email Photo Alert,Snapshot and Record uploaded to FTP
Network	Ethernet Interface	One 10/100Mbps RJ-45
	Supported Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP etc.
	Online Visitor	Support Max 6 visitors at the same time (First Stream:3 visitors;Second Stream:3 visitors)
	IP Mode	Dynamic IP address, static IP address(DHCP)
	Online Visitor	Support Microsoft Win XP/Win7/Win8/ win10/Mac OS.
	Browser	Support Internet Explorer 8.0-11.0, FireFox,Google Browser
	One key setting Function	Support one key setting function connect WIFI
	Wireless Standard	WIFI, 802.11b/g/n
Others	OSD	Support the OSD name, date and time info superposition (Open/Off)
	Product Type	Outdoor Use
	Power	DC5V/2A

	Working Temperature	-10~50 °C
	Working Humidity	95% RH
	Size	Item: 148 x 60mm (HxW); Packaging: 175 x80 x95 mm (LxWxH)
	Weight	N.W.: 289g G.W.: 461g (Note:Actual Weight Final)
Certification	CE,FCC,RoHS	
Warranty	Limited 2-Year Warranty	