

CCTV / HD 4n1 / Cameras

SF-D935UW-2P4N1

Starlight IR Solution 4N1 Camera

Starlight PRO Series

High sensitivity Starlight 0.005Lux sensors, to obtain a great performance in low light situations that use IR illumination. The solution is powered by 3DNR noise reduction and a Sense-Up slow-speed shutter. Wide dynamic range (WDR) of 120 dB solves any situation of backlight or high light contrast.

- 1080p Resolution
- Starlight CMOS Sensor
- 2.8 mm Fixed Lens
- Smart IR Up to 30 m
- WDR | 3D DNR Advanced functions
- IP67 Weatherproof
- IK10 Vandalproof



Technical Specification

Image Sensor	2 MP CMOS image sensor
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s, NTSC: 1/30 s to 1/50, 000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°; Tilt: 0° to 75°; Rotate: 0° to 355°
Lens Type	2.7 mm to 13.5 mm motorized varifocal lens
Focal Length & FOV	95.7° to 29.1°
Lens Mount	□ 14
Image Settings	Brightness, Sharpness, 3D DNR, Mirror, Smart IR
Frame Rate	PAL: 1080p@25fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	DWDR
Image Enhancement	BLC
White Balance	ATW/MWB
AGC	Support
Video Output	Switchable TVI/AHD/CVI/CVBS
Material	Metal
Dimension	Ø 145 mm × 111.3 mm (Ø 5.70" × 4.37") Approx. 815 g (1.80 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	Up the coax, Protocol: Safire-C (TVI output)
Power Supply	12 VDC ±15%, 24 VAC ±15%
Consumption	Max. 4.4 W
IR Range	Up to 30 m
Protection	IP67, IK10