

KV-2CD2T47G2P

4MP Dual illumination Panoramic Network Camera



Key Features

- 2 x 1/2.9" GC2063 CMOS
- 3840 × 1080@20 fps
- 2 x 4 mm fixed lens
- H.265+, H.265, H.264
- F1.6 lens
- Built-in Microphone
- White Light & IR Range: up to 30 m
- WDR/HDR/3D DNR/HLC/BLC
- Water and dust resistant(IP67)
- Color: 0.05 lux @(F1.6), 0 lux with IR light
- Angle adjustment

Specifications


Camera	
Image Sensor	1/2.9" GC2063 CMOS
Min. Illumination	Color: 0.05lux @(F1.6), 0 lux with IR light
Shutter Speed	1/10 s to 1/10,000 s
Slow Shutter	Yes
Day & Night	IR CUT Filter
Digital Noise Reduction	3D DNR 2D DNR
WDR	120dB
Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 180°, rotate: 0° to 360°
Lens	
Focal Length	Fixed focal lens,dual lens, 4 mm
Aperture	F1.6
Focus	Fixed
Focus Length & FOV	4 mm, horizontal FOV: 170°, vertical FOV: 40°
Lens Mount	M12
Illuminator	
White Light & IR Range	Up to 30 m
Smart Supplement Light	Yes
Compression Standard	
Video Compression	Main stream: H.265+/H.265/H.264 Sub-stream: H.265+/H.265/H.264
H.264 Type	High Profile/Main Profile/Base Profile
H.265 Type	High Profile/Main Profile/Base Profile
H.265+	High Profile/Main Profile/Base Profile
Smart Feature-set	
Smart Event	Human detection
Basic Event	Motion detection
Linkage Method	Trigger recording: memory card, network storage, pre-record and post-record Trigger captured pictures uploading: FTP, HTTP, NAS, Email Trigger notification: HTTP, Email
Image	
Max. Resolution	3840 × 1080
Main Stream	50Hz: 20 fps 3840 × 1080 60Hz: 20 fps 3840 × 1080
Sub-Stream	50Hz: 20 fps 1280 x 360 60Hz: 20 fps 1280 x 360

Image Enhancement	WDR/HDR/3D DNR/2D DNR/HLC/BLC
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness, and white balance adjustable by client software or web browser
SVC	H.264 and H.265 encoding support
Day/Night Switch	Day/Night/Auto/Schedule
Network	
Network Storage	Support local storage and NAS (NFS, SMB/CIFS)
Protocols	HTTP, RTSP, DHCP, FTP, NTP, ONVIF, P2P, SMTP, RTMP
Client	AJ_Client, AC18Pro, Videolink
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Built-in Microphone	Yes
Built-in Speaker	Power: 3W.MAX. Sound pressure lever:10cm: 100dB.
Reset Key	Yes
On-Board Storage	Built-in memory card slot, support micro SD card, up to 512GB
General	
Operating Conditions	-30 °C to +85 °C, humidity 95% or less (non-condensing)
Web Client Language	14 languages: English, Russian, German, Italian, Turkish, Korean, Japanese, Traditional Chinese, Simple Chinese, Ukrainian, Portuguese, Croatian, Polish, Farsi
Power Consumption and Current	DC 12V, 1 A, max. 10 W Φ 5.5X2.1 mm coaxial plug power PoE (802.3af, 36 V to 57 V), 0.35 A to 0.22 A, max. 12.5W
Protection Level	IP67-Each Camera has been tested waterproof
Material	Front cover:metal,body:metal,bracket:metal
Dimensions	Camera: 236.1 × 110 × 74mm (9.29" × 4.33" × 2.91") Package: 325 × 125 × 120 mm (12.8" × 4.92" × 4.7")
Weight	Apporx.650g(1.43 lb)
With Package Weight	Apporx.800g(1.76 lb)

Available Model

KV-2CD2T47G2P (4mm 170°)

Dimension



Accessory

Bracket DS-1280ZJ-S

